

AMENDMENTS

In the Claims

1. **(Currently Amended)** A method comprising:
providing information relating to a business application in a server system, comprising
receiving a request, wherein
the request is configured to cause the business application to execute a
command of the business application,
the request comprises an indication of a user interface element to be
returned,
the command is configured to be defined by a data structure comprising
an execute element,
a command element, and
an argument element, and
the command element represents a predefined query;
generating a data element by executing the command of the business application;
generating the user interface element ~~to be returned in response to the request,~~
wherein
the user interface element comprises a configurable subset of the data,
and
sending a response comprising the user interface element and the data element;
~~wherein the user interface element and the data element are XML~~
~~documents.~~
2. **(Previously Presented)** The method of claim 1 wherein the argument element
indicates a type of user interface element to return.
3. **(Previously Presented)** The method of claim 1 wherein the argument element
indicates a type of user interface element to not return.

4. (Original) The method of claim 3 wherein the type of user interface element not to return is navigation data.

5. (Previously Presented) The method of claim 1 wherein the argument element comprises an “SWEDataOnly” argument.

6. (Previously Presented) The method of claim 1 wherein the argument element comprises an “SWEApplet” argument.

7. (Previously Presented) The method of claim 1 further comprising:
receiving a list of predefined queries in response to the request, wherein
the list of predefined queries comprises the predefined query.

8. **(Currently Amended)** A method in a server system for providing information relating to a business application, the method comprising:
- providing transforms for transforming output of the business application, each transform having a name;
 - receiving a request to execute a command of a business application, wherein
 - the request is received from a client system,
 - the command is configured to be defined by a data structure comprising
 - an execute element,
 - a command element, and
 - an argument element,
 - the command element represents a predefined query, and
 - the argument element optionally indicates the name of a transform to be applied to the output of the business application;
 - generating a data element by executing the command of the business application,**
 - ~~generating a generated output by executing the command of the business application,~~
 - ~~wherein the request is in XML format and the transforms are XSLT~~
 - stylesheets from a configurable subset of the data;**
 - when the argument element indicates the name of the transform,
 - generating a transformed output by applying the transform to the generated output, and
 - sending the transformed output to the client system; and
 - otherwise, sending the generated output to the client system.
9. **(Cancelled)**
10. **(Previously Presented)** The method of claim 8 wherein the request comprises an “SWEShStyleSheet” argument.

11. **(Currently Amended)** A method in a server system for providing information relating to a business application, the method comprising:
- providing a default format for output of the business application;
 - receiving a request to execute a command of a business application,
 - the request is received from a client system,
 - the command is configured to be defined by a data structure comprising
 - an execute element,
 - a command element, and
 - an argument element,
 - the command element represents a predefined query, and
 - the argument element optionally indicates a user agent format or a client-specified format for the output of the business application;
 - selecting a format giving preference in the following order: the client-specified format, the user-agent format, and the default format;
 - generating a data element by executing the command of the business application,**
 - generating a generated output by ~~executing the command of the business application,~~**
 - ~~wherein the request is in XML-format~~ from a configurable subset of the data;**
 - sending the generated output in the selected format to the client system.
12. **(Original)** The method of claim 11 wherein the user-agent format is selected over the default format in accordance with a predefined preference of formats.
13. **(Original)** The method of claim 11 wherein the user-agent format is based on type of user agent specified in the request.
14. **(Original)** The method of claim 13 wherein the type of user agent specifies a type of browser.
15. **(Original)** The method of claim 11 wherein the formats are a markup language.
16. **(Original)** The method of claim 15 wherein one of the formats is HTML.

17. (Original) The method of claim 15 wherein one of the formats is XML.
18. (Original) The method of claim 15 wherein one of the formats is WML.
19. (Previously Presented) The method of claim 11 wherein the request comprises an “SWESetMarkup” argument that specifies the client-specified format.
20. (Currently Amended) A computer-readable storage medium containing: first instructions, executable on a first computer system, configured to execute a first command of a first business application; ~~and~~ second instructions, executable on a second computer system, configured to execute a second command of a second business application; and a common data structure defining the ~~command~~ first command and the second command, wherein the ~~command is~~ first command and the second command are inbound to a web server ~~and the web server is configured to execute on the computer system~~, the data structure comprising an execute element having a path attribute indicating a location of an object manager, a command element nested within the execute element and having a value attribute indicating a name of the command, wherein the command element represents a predefined query, and one or more argument elements nested within the command element, each argument element having a name attribute indicating a name of an argument for the command, the one or more argument elements being from a set of argument elements comprising an argument element for indicating a response markup format, an argument element for indicating whether the response should include user interface elements, and an arguments element identifying a transform to be applied to output, ~~wherein the data structure is an XML document.~~
21. (Cancelled)

22. (Currently Amended) The computer-readable storage medium of claim 20 wherein zero or more occurrences of the command element are nested within the execute element.

23. (Currently Amended) The computer-readable storage medium of claim 20 wherein only one command element is nested within the execute element.

24. (Currently Amended) A computer-readable storage medium containing: first instructions, executable on a first computer system, configured to execute a first command of a first business application; ~~and~~ second instructions, executable on a second computer system, configured to execute a second command of a second business application; and a common data structure defining the ~~command~~ first command and the second command, wherein the ~~command is first command and the second command~~ are outbound to a web server ~~and the web server is configured to execute on the computer system~~, the data structure comprising an application element having a name attribute,

- a navigation element nested within the application element, having a name attribute, and having sub-elements from a set comprising a menu element, tool bar element, screen bar element, thread bar element, view bar element, and page item element,
- a predefined query bar element nested within the application element and each having a name attribute, and
- one or more elements from the set of elements comprising a screen element, an applet element, and a form element, the one or more elements being nested within the application element and each having a name attribute, ~~wherein the data structure is an XML document.~~

25. (Previously Presented) A method in a server system for providing information relating to a business application, the method comprising:

receiving a request to execute a command of a business application, wherein
the request is received from a client system,
the command is configured to be defined by a data structure comprising
an execute element,
a command element, and
an argument element,
the command element represents a predefined query, and
the argument element indicates a user interface element and a data element to be
returned as results of execution of the command;
generating the data element by executing the command, wherein the user interface
element and the data element are XML documents;
when the argument element indicates to return at least one user interface element,
generating the at least one user interface element to be returned; and
sending a first response to the client system, wherein the first response comprises
the at least one user interface element and the data element; and
otherwise, sending a second response to the client system, wherein the second response
comprises the data element and the second response does not include the user
interface element.

26. (Original) The method of claim 25 wherein the request indicates a type of user interface element to return.

27. (Original) The method of claim 25 wherein the request indicates a type of user interface element to not return.

28. (Original) The method of claim 27 wherein the type of user interface element not to return is navigation data.

29. (Previously Presented) The method of claim 25 wherein the request comprises an “SWEDataOnly” argument.

30. (Previously Presented) The method of claim 25 wherein the request comprises an “SWEApplet” argument.

31. (Previously Presented) The method of claim 25 further comprising:
receiving a list of predefined queries in response to the request, wherein
the list of predefined queries comprises the predefined query.